

3.000



UHP 220

Type	Cold-water ultrahigh-pressure unit
Working pressure	Up to 2,800 bar (40,600 PSI)
Flow rate	Max. 27 l/min (7.13 USgal/min)
Pump	Low-speed ultrahigh-pressure pump with 3 carbide plungers, integrated reduction gearbox, power-end cooler and pressure oil lubrication
Motor	VOLVO PENTA 4-cylinder diesel, water-cooled; 5,200 cm ³
Motor output	160 kW (220 HP)
Speed of motor & pump / Drive	2,065/500 rpm / Gearbox
Fuel consumption	Approx. 21 l/h (5.56 USgal/h)
Volume of fuel tank	200 l (52.83 USgal)
Volume of urea tank	25 l (6.60 USgal)
Urea consumption	Approx. 1.05 l/h (0.27 USgal/h)
Discharge coupling (water)	9/16"-18 UNF LH IT or DYNAJET EC Easy Connect
Chassis	2-axle trailer
Unladen weight	2,690 kg
Dimensions (L x W x H)	467 x 197 x 218 cm
Dimensions when open (L x W x H)	487 x 310 x 254 cm
Article number	1 610 040
Stationary version	UHP 220 s, Article number 1 610 140

DYNAJET GmbH
German Technology



Middle East Petromechanic
Exclusive Agent of DYNAJET

Tel/Fax : +98 (21) 44111245 , 44137379

Email: info@petromechanic.com

Website: www.petromechanic.com